


Do more with A4.

The TASKalfa 408ci is a powerful A4 colour MFP for small to medium sized workgroups in medium to large corporate environment where durable operations and flexible finishing are required. A renewed 7" operation screen with intuitive operation such as scroll and slide, pinch in/pinch out like smartphones and tablets. Advanced security functionality like secure boot, Trusted Platform Module (TPM) and standard Data Security Kit.



Specifications

GENERAL

KYOCERA TASKalfa Laser Colour Multifunctional, HyPAS™ solution platform

Operation panel: Smart intiutive new user interface, 177.8 mm (7 inch) full-colour touch panel with scroll and slide smartphone/ tablet operability, 0-90° swivel mounted

Engine speed: Up to 40 pages A4 per minute, Duplex print speed: 40 pages A4 per minute

Resolution: 1,200 × 1,200 dpi print at reduced speed, multibit

technology for print quality of up to $9,600 \times 600 \, \text{dpi}$ (print), 600 × 600 dpi (scan/copy)

Warm-up time: Approx. 21.8 seconds or less Time to first print: Approx. 5.4/6.4 seconds or less in

Monochrome/Coloui

Time to first copy: Approx. 5.8/6.9 seconds or less in Monochrome/Colour (Platen)

CPU: Freescale QorlQ T1042 (Quad Core) 1.0 GHz

Memory: 4GB RAM, 8GB SSD, 320 GB HDD Standard interfaces: 3 × USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), USB 2.0 (Hi-Speed), 2 eKUIO slots for optional internal print server, fax system, slot for optional SD Card, NFC tag Integrated accounting: 1,000 department codes

Dimensions (W \times D \times H): 550 mm \times 508 mm \times 612.8 mm Weight: 49.3 kg

Power source: AC 220-240 V, 50/60 Hz

Power consumption: Copy/Print Mode: Mono 652 W/Color 652 W; Low Power Mode: 52 W; Ready Mode: 84 W; Sleep Mode: 0.7 W Noise (sound pressure level: ISO 7779/ISO 9296):

Copying/Printing: $68.2 \, dB(A) \, L_{pA}$ Stand-by: $45 \, dB(A) \, L_{pA}$

Safety standards: This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Multi-purpose tray: 100 sheets, 60-220 g/m² (Banner 129–163 g/m²), A4, A5, A6, B5, B6, Letter, Legal, Custom (70 \times 148 to 216 \times 356 mm), Banner max. 216 \times 1,220 mm; Standard universal paper cassette: 500 sheets, $60-220\,\mathrm{g/m^2}$, A4, A5, A6, B5, B6, Letter, Legal, Custom (105×148 to $216\times356\,\mathrm{mm}$); Max. input capacity with options: 3,100 sheets A4

Duplex: Standard Duplex unit: 60–220 g/m², A4, A5, B5, Letter,

Output capacity: Standard 500 sheets face-down with paper full

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc Emulations: PCL6 (PCL-XL/PCL-5c) , KPDL 3 (PostScript 3

compatible), PDF Direct Print, XPS Direct Print **Operating systems:** All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417) Mobile printing support: KYOCERA Mobile Print app for

iOS and Android, AirPrint, Mopria, Wi-Fi Direct, Google

cloud print, DSK standard

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job nanagement functionality

COPY FUNCTIONS

Max. original size: A4/Legal Continuous copying: 1 – 9,999 Zoom range: 25 – 400 % in 1 % steps

Preset magnification ratios: 5 Reductions/5 Enlargements Exposure mode: Auto, manual: 9 steps

Image adjustments: Text + Photo, Photo, Text, Map, Printed

Features: Scan-once-copy-many, electronic sort (collate), ID card copy, 2in1, 4in1, auto cassette change, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Network TWAIN, WIA, WSD scan Scan speed: DP-5100 up to 60 ipm; DP-5120 up to 120 ipm; DP-5130 up to 170 ipm

Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per colour Max. scan size: A4, Legal, Banner up to 1,900 mm

Original recognition: Text, photo, text + photo, light text/fine line, optimised for OCR

File types: TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPG compression/high compression PDF), Searchable PDF (Option), MS Office file (Option)

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3

Fax Memory: 170 MB

Modem speed: Max. 33.6kbps

Transmission time: Max. 3 seconds (JBIG)

Scanning speed: 2.0 seconds or less Address book: 2,000 entries

Fax resolution:

Normal: 8 dot/mm × 3.85 line/mm (200 × 100 dpi) Fine: 8 dot/mm \times 7.7 line/mm (200 \times 200 dpi) Superfine: 8 dot/mm × 15.4 line/mm (200 × 400 dpi) Ultrafine: 16 dot/mm \times 15.4 line/mm (400 \times 400 dpi)

Halftone: 256 grevscales

Maximum original size: A4/Legal, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with

TK-5315K Toner Kit: Microfine toner black for 24,000 pages A4 TK-5315C, TK-5315M, TK-5315Y Toner Kit: Microfine toner cyan, magenta, yellow for 18,000 pages A4

WT-5191 Waste Toner Bottle: 44,000 sheets (in accordance with 5% coverage; Monochrome/Colour=7:3) Staples: SH-10 for DF-5100/DF-5110/DF5120, $3\times 5{,}000$

Fax System 10 (X): max. 2: Super G3 Fax, network Fax Internet Fax Kit (A): Option for Fax System 10(X), T.37 via SMTP/

DP-5100 Reverse Document Processor: 75 sheets, 50-120 g/m² DP-5120 Dual Scan Document Processor:

100 sheets, 50–120 g/m²

DP-5130 Dual Scan Document Processor: 270 sheets with double feed detection, staple detection, 50–120 g/m

PF-5120 Paper feeder: 500 sheets, 60 $-220\,\mathrm{g/m^2}$; A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 × 148 mm to 216 × 356 mm) PF-5130 Paper feeder 1 : 2 × 500 sheets, 60–220 g/m 2 ; A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 × 148 mm to 216 × 356 mm) PF-5140 Paper feeder¹: 2,000 sheets, 60–220 g/m²; A4, Letter DT-5100 Document tray: To place originals or USB Keyboard

JS-5100 Job separator: 100-sheet internal job separator, 60–220 g/m²; A6–A4, Legal

MT-5100 5-Bin Mailbox sorter²: 5 bins × 100 sheets A4, 60-163 g/m², Main tray: 500 sheets A4, 60-220 g/m DF-5100 Internal Document Finisher: 300 sheets 60-220 g/m², oling up to 50 sheets A4 at 2 positions

DF-5110 External Document Finisher²: 1,000 sheets $60-220\,\mathrm{g/m^2}$, Stapling up to 50 sheets A4 at 2 positions

PH-5110 Punch Unit: for DF-5110, 2-hole/4-hole, 60-220 g/m², A4 DF-5120 External Document Finisher²: 3,000 sheets $60-220\,\mathrm{g/m^2}$, Stapling up to 50 sheets A4 at 2 positions Punch unit included: 2-hole/4-hole, $60-220\,\mathrm{g/m^2}$, A4

Sub tray: Max. 200 sheets A4, 660—220g/m UG-33: ThinPrint support

UG-34: Emulation (IBM Proprinter/EPSON LQ-850/LinePrinter)

USB IC Card Reader + Card Authentication Kit (B):

Supports various authentication card keys IC Card Reader Holder 11: To integrate the USB IC Card

Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx) Optional interfaces:

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)

IB-51: Wireless LAN (802.11b/g/n)

IB-35: Direct Wi-Fi Interface NK-7100(B): Numeric keypad

CB-5110H Cabinet: Wooden desk with storage capacity, approx. $55 \text{ cm} \times 51 \text{ cm} \times 50 \text{ cm} (W \times D \times H)$

CB-5110L Cabinet: Wooden desk with storage capacity, approx. $55\,\text{cm}\times51\,\text{cm}\times34\,\text{cm}$ (W \times D \times H) CB-5120H Cabinet: Metal desk with storage capacity,

approx. $55 \text{ cm} \times 51 \text{ cm} \times 50 \text{ cm} (W \times D \times H)$ CB-5120L Cabinet: Metal desk with storage capacity,

approx. $55 \text{ cm} \times 51 \text{ cm} \times 34 \text{ cm} (W \times D \times H)$

Requires PF-5120

Bridge unit AK-5100 is required for the use of MT-5100, DF-5110, DF-5120

The TASKalfa 408ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 408ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.













KYOCERA Document Solutions Partner

JANUARY2020DSTASKALFA408CI/VER1.0

KYOCERA Document Solutions South Africa 90 Bekker Road, Hertford Office Park, Vorna Valley, Midrand Tel (011) 595 2600 www.kyoceradocumentsolutions.co.za - info@dza.kyocera.com



kyoceradocumentsolutions.co.za